BILSON DOOR

Pre-Assembled Exterior Door - Engineered for the Modular Industry



KERF FRAME

The 16GA Kerf Frame is specially designed to hold weather stripping in place without screws or adhesive. This creates a tight seal - keeping out water, air, and debris.



PREP

All doors prepped for 161 lever and either Invisible Deadbolt (IDB) or Bored Deadbolt Prep (DB).

SWEEP & THRESHOLD

36 inch sweep paired with an ADA saddle threshold.



LITE KIT

A variety of options including no lite kit, 12 x 12, 8 x 32, or a custom size to fit your needs.

POWDER COAT FINISH

Powder coating provides a high-quality, durable finish that resists scratching, flaking, and fading. It also offers a smooth surface that's easy to repaint if needed.



PDQ HINGES

Standard 4.5 x 4.5 inch BB NRP hinges - Made from corrosion-resistant materials.

BILSON

- Rough Opening: 36" x 80" - Door Size: 34 3/4" x 78 1/8"

- Overall Dimensions: 38 5/8" x 81 5/16"

BILSON XL

- Rough Opening: 38" x 81"

- **Door Size:** 35 3/4" x 79 1/8" (3068)

- Overall Dimensions: 40 1/4" x 82 3/32"

PRE-HUNG DOOR	 - 20 Gauge hollow metal - 20 Gauge top cap - 16 Gauge end channels - Polystyrene foam core - Reinforced for door closer - Various lite kit options - Powder coat finish
KERF FRAME	16 Gauge hollow metalKerf frame profileFlange mountedASA strike prepPowder coat finish
ACCESSORIES	- PDQ BB NRP Hinges- Kerf weather stripping- ADA saddle threshold- Door sweep
COLORS	WhiteOff-WhiteGrayDark GrayBronze





CONTACT THE BT TEAM:

Vice President:

CortneyMilbourne@bt-modular.com

National Sales Manager:

HeatherBrendle@bt-modular.com

Website:

www.bt-modular.com

Phone:

833.444.7795

Address:

2230 Embassy Dr Lancaster, PA 17603

